



## Features

- Can use multiple liquid fuel types (JP-8/F-24, F-34 "NATO", gasoline, isopropanol, Kerosene/Paraffin, AVGAS, Jet-A/Jet-A1, JP-5, JP-4, propane capable - UPAK required \*)
- Twin Tech parallel function allows two units connected together to provide 3kW/30 AMPs of rated power.
- Lightweight, "Man Portable"
- Quiet, small noise signature
- Plug-in compatible with Trinity™ Systems or stand-alone
- Immediate functionality on startup - No waiting
- Auto turn down when load is low
- Low maintenance, Easy to operate
- 2,000 hour/1 year limited warranty (repair or replace)
- Tunable for high elevation

## Includes

- 1x IntelliGEN™ 2200 Flex-Fuel Generator v1.0 (p/n INI-IG2200)
- 1x Initial Oil Fill Bottle
- 1x 12.5' Extended Exhaust Piping w/ Clamp
- 1x 2kW Maintenance Kit
- 1x Operator Manual
- 2x Cold start canister (Removed for Air shipment)
- 2x Quart 15W40 Small Engine Oil
- 1x Quick Reference Card

*\*Unit will operate on diesel in an emergency, but engine oil will need to be changed every 4 hours or at refueling, whichever comes first*

## Specs

- Start System: Manual Recoil Start
- Max Peak Output: 2200W (Sea Level) (Gasoline and JP-8/F-24)
- Gasoline Nominal Output: 1800W (Sea Level)
- Gasoline Nominal Voltage: 120VAC, 60Hz, 12VDC
- JP-8/F-24 Nominal Output:
  - Certified to 1500W (Sea Level)
- JP-8/F-24 Nominal Voltage: 120VAC, 60Hz, 12VDC
- AC Output Power outlets: 15A (2), 30A (1)
- DC Output Power outlets: 12V 3A (1)
- Dry Weight: 61 lbs. (27.7 kgs)
- Dimensions: 21.9" x 11.8" x 18.5" (557 mm x 300 mm x 470 mm)
- Gasoline Operating Temp: -4,F to 122,F (-20°C to 50°C)
- JP-8 Operating Temp: 14,F to 122,F (-10°C to 50°C)
- Storage Temp: -40°F to 176°F (-40°C to 80°C)
- Operating Elevation: Sea Level to 10,000 ft. (3048 m)
- Internal Tank: 1.2 gal (4.5 L)
- Color: Tan or Green
- Part Number: INI-IG2200